



**AmericanBiltrite**  
Flooring

## ABPURE® Nfuse® Infinity Carbon Neutral RUBBER SHEET

### TECHNICAL SPECIFICATIONS

	Series	Metric	Imperial
Gauge	ABI	3 mm	0.118"
Sizes: Sheet	ABI	1.52 m x Up to 15.2 m	59.75" x Up to 50'
Product Classification: ASTM F1859 - Rubber Sheet Floor		Type 1 (Homogeneous)	
ASTM D2047 - Static Coefficient of Friction (leather/Neolite)		≥ 0.5	
ASTM D3389 - Abrasion Resistance (H-18,500 g @ 1,000 cycles) (TILES)		Pass	
ASTM E648 - Critical Radiant Flux CRF (W/cm <sup>2</sup> )		≥ 0.45	
ASTM E662 - Smoke Density		≤ 450	
ASTM E989 / E492 - Sound Absorption (with a suspended ceiling)		IIC 59	
ASTM F925 - Chemical Resistance		Exceeds	
ASTM F970 - Static Load		≤ 0.005"	
ASTM F1514 - Heat Stability		ΔE ≤ 8.0	
ASTM F1515 - Light Stability		ΔE ≤ 8.0	
ASTM G21 - Antimicrobial Resistance Test		Pass (28 days)	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)		FloorScore Certified by SCS Certification Registration Number SCS-FS-01492	
Adhesives: AD-777: Regular traffic AD-590: Heavy rolling loads, under patients' beds, non-acclimatized areas AD-599MR: High Moisture Substrate, Heavy rolling loads, under patients' beds, non-acclimatized areas AB-READYTAPE-99 (Sheet only): Occupancy Ready, High Moisture Substrate, Regular traffic			
Limited Wear Warranty		10 years	
Resistance to oils and greases			
ABPURE® is not recommended for environments where it could be exposed to oils and greases, whether mineral, animal or vegetable.			
Antimicrobial			
<b>IMPORTANT:</b> All our ABPURE rubber flooring, through its composition and without the use of antimicrobial chemicals, does not promote microbial growth.			

Please note that technical web site documents prevail.

