

Wild
Woven Vinyl

ntgrate®

GEO FLOORING



WILD WOVEN VINYL



*Wild
Woven vinyl by ntgrate.*

*Simple, Sophisticated, a Modern
Fashionista of Impetuous
Patchwork.*

WILD WOVEN VINYL



WILD WOVEN VINYL



WILD WOVEN VINYL



Jade (LRV - 16.7)



Julia (LRV - 26.1)

The Light Reflectance Value (LRV) indicates the extent to which the light is reflected from a surface illuminated by a light source. It refers to the total amount of visible and usable light (of all wavelengths and in all directions) reflected from all surfaces present.



Leon (LRV - 22.4)



Milo (LRV - 13.0)

WILD WOVEN VINYL



WILD WOVEN VINYL



WILD WOVEN VINYL

Technical Product Information		
Available Sizes		Tiles
Weight	ISO 8543	3 kg /m ²
Thickness	ISO 1765	4.7 mm
Dimensions	EN 984	50 x 50 cm
Backing		Greenfelt 19
Level of use / Wear Rating*	EN 1307	Class 33
Dimensional Stability	EN 986	< 0.2%
Suitable for Castor Chairs	EN 985	Intensive Use
Static Loading	ISO 1815	< 2 kV
Impact Sound Reduction**	ISO 10140	19dB
Acoustical Absorption**	ISO 354	15%
Drum Sound Reduction (foot-fall)**	EN 16205	71 dB (A)
Light Fastness	EN 105-B02	≥ 7
Fire Rating	ISO 9239.1	Pass
Resistance to Fraying	EN 1814	Very Good
Stain Resistance	EN 423	Very Good
Slip Resistance	AS4586-2013-A	P2

* LEVEL OF USE / WEAR RATING - The European Standard for classification of all textile floorcoverings, Class 33 means the product is suitable for Heavy Commercial use (i.e. Public Spaces and high traffic areas).

** ACOUSTICS

- Impact Sound is the sound you perceive in the space and is reduced by 19dB.
- The textile structure of the **ntgrate** floor covering achieves a high acoustic absorption value of 15%, compared to 5% achieved by conventional vinyl floors.
- Drum Sound is footfall or walking sound achieves 71dB, compared to conventional vinyl floors of 80dB. For every reduction of 3dB, there is a 50% reduction of perceived sound, or doubling of comfort.

MAINTENANCE

Easy daily maintenance by vacuuming. Most stains easily removed with a clean cloth and water. Less periodic maintenance required by following simple preventative steps for increased longevity and perfect hygiene.

Sustainability

All **ntgrate** floor coverings contribute to a healthy living and working environment, and have been independently certified to the highest levels.

ntgrate believes in a sustainable future and resolutely and exclusively opts for sustainable investments. They lead by example and all of their production and offices are housed in a their new BREEAM certified building in Kortrijk, Belgium.

As responsible manufacturers, **ntgrate** strive for a sustainable future and focus on circular construction.

- All energy used during manufacturing is from renewal resources and their solar panels.
- Rainwater is collected and reused.
- 100% of waste is recycled at authorised partners for reuse into other items.
- **ntgrate** is 100% recyclable and is used in temporary road plates.
- 66.4% from natural raw materials or recycled materials.





www.geoflooring.com.au
info@geoflooring.com.au
+61 2 9960 4199

